

# Tube-U (N)

## 802.11 b/g/n Long Rang Outdoor USB AP/CPE with N-Type Connector



Tube-U(N) is the long-range wireless 802.11b/g/n outdoor USB CPE with 5M usb cable. Tube-U(N) provides users to launch IEEE 802.11n wireless network at 150 Mbps in the 2.4GHz frequency, which is also compatible with IEEE 802.11b/g/n wireless devices at maximum 150Mbps. You can easy to install and enjoy the internet connection by just simply plug USB into the Notebook and Desktop. Tube-U(N) also includes a convenient Utility for scanning available networks and saving preferred networks that users usually connected with. Security encryption can also be configured by this utility.

### Product Features:

- Complies with Universal Serial Bus Rev. 1.0, 1.1 and 2.0 specifications.
- High-Power 1W with N-type female antenna connector for long-Range Distance.
- High Speed transfer data rate up to 150Mbps
- Supports WPS by software
- 2.4GHz frequency band, MIMO (Multiple Input Multiple Output)
- Support wireless data encryption with 64/128-bit WEP, WPA (TKIP with IEEE 802.1x) and AES functions.
- Support driver for Windows 98se, Me, 2000, XP and Vista, Windows 7, Apple Mac and Linux.
- Supports auto-installation and diagnostic utilities.

### For further details:

Alfa Network Inc.,  
4F-1 No. 106, Rueiguang Rd.,  
Neihu District,  
Taipei City, Taiwan.  
<http://www.alfa.com.tw>  
sales@alfa.com.tw

Tel:+886-2-27968477 | Fax:+886-2-27968478




# Tube-U


## 802.11 b/g Long Rang Outdoor USB AP/CPE with N-Type Connector

### Specification:

Standards	IEEE 802.11b/g/n USB v1.0/1.1/2.0
USB Cable Length	5M
Data Rate	IEEE 802.11g 54Mbps IEEE 802.11b 11Mbps IEEE 802.11n 150Mbps
Output Power	30dBm
Receiver Sensitivity	IEEE 802.11n: -90dBm @ HT20 IEEE 802.11g: -92dBm @ 54Mbps IEEE 802.11b: -95dBm @ 11Mbps
Antenna	External N type Female Antenna Port
Frequency	US, Canada 2.412GHz~2.462 GHz (CH1~CH11) EU 2.412GHz~2.472GHz (CH1~CH13) Japan 2.412GHz~2.484GHz (CH1~CH14)
Security	64/128-bit WEP Encryption, WPA, WPA2, TKIP, AES, Cisco CCX, WAPI-PSK, and WAPI-CERT
Support OS	Windows XP/2000/Vista, Windows 7, Linux, Mac X
Operating Voltage	DC 5V ± 5%
Temperature	Operating: 0°C ~ +50°C Storage : -10°C ~ +65°C



Plastic Straps



CD



USB Cable 5M